TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

Revision date 02-Jan-2020 Supersedes Date: 02-Jan-2020

1. Identification

1.1. Product Identifier

Product Name

TSC-300 Outdoor-Indoor Carpet Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Uses advised against Adhesives. No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

TSC International Products, LLC PO Box 1005 Chatsworth GA 30705 USA Phone: +1 (706) 517-3599

1.4. Emergency telephone number

Telephone: Chemtrec:800-424-9300

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200

2.2. Label Elements

EMERGENCY OVERVIEW Not a dangerous substance or mixture according to OSHA 29 CFR 1910.1200. Appearance Paste Physical State Liquid Odor Characteristic Precautionary Statements - Prevention Not applicable Precautionary Statements - Response Vertice Precautionary Statements - Storage Not applicable Precautionary Statements - Storage Vertice Precautionary Statements - Disposal Disposal Disposal Disposal

TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

Not applicable

Hazards not otherwise classified (HNOC) Not applicable

2.3. Other Information

No information available.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical name	CAS No.	Weight-%
Feldspar	68476-25-5	10 - 30
Kaolin	1332-58-7	10 - 30
Quartz	14808-60-7	1 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. If eye irritation persists: Get medical advice/attention.		
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician.		
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.		
Ingestion	Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.		
4.2. Most important symptoms and effects, both acute and delayed			
Symptoms	No information available.		
4.3. Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		
4.4. Reference to Other Sections			
Reference to other sections	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION Section 11: TOXICOLOGY INFORMATION		

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Water spray (fog). Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local

TSC-300 Outdoor-Indoor Carpet Adhesive

Revision Number 2

circumstances and the surrounding environment.

Unsuitable extinguishing media None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

Explosion Data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

5.3. Advice for firefighters

Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protection recommended in Section 8.		
6.2. Environmental precautions			
Environmental precautions	Keep people away from and upwind of spill/leak. See Section 12 for additional Ecological Information.		
6.3. Methods and material for conta	inment and cleaning up		
Methods for containment	Stop leak if you can do it without risk.		
Methods for cleaning up	Use personal protective equipment as required. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Dam up. Cove liquid spill with sand, earth or other non-combustible absorbent material.		
6.4. Reference to other sections			
Reference to other sections	Section 7: HANDLING AND STORAGE Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION		

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wash hands thoroughly after handling. Do not reuse container.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing. Keep containers tightly closed in a cool, well-ventilated place.

Section 13: DISPOSAL CONSIDERATIONS

TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

Incompatible materials	No information available.
7.3. Specific end use(s)	
Specific Use(s) Adhesives.	
Other information	No information available.
7.4. References to Other Sections	
Reference to other sections	Section 13: DISPOSAL CONSIDERATIONS Section 10: STABILITY AND REACTIVITY
Section 8: EXPOSURE CON	TROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

. This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Feldspar 68476-25-5	2 mg/m ³ (Respirable fraction)	-	-	-
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 2 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m ³ TWA respirable fraction	TWA: 0.025 mg/m³

Chemical name	Argentina	Brazil	Chile	Venezuela
Kaolin 1332-58-7	TWA: 2 mg/m ³	-	TWA: 13 mg/m ³ TWA: 4.5 mg/m ³	TWA: 2 mg/m ³
Quartz 14808-60-7	TWA: 0.05 mg/m ³	-	TWA: 0.08 mg/m ³	TWA: 0.025 mg/m ³

8.2. Exposure controls

Engineering controls

Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas. Use explosion-proof ventilating equipment.

Personal protective equipment [PPE]

Eye/face protection Skin and body protection

Respiratory protection

Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be

TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

Revision date 02-Jan-2020 Supersedes Date: 02-Jan-2020

required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Remarks • Method

General hygiene considerations Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Avoid contact with eyes, skin and clothing. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical a	nd chamical proportios	
Physical state	Liquid	
Appearance	Paste	
Color	White or light brown	
Odor	Characteristic	
Odor threshold	No information available	
Property	Values_	Remarks •
pH	7.5 - 8.5	
Melting point / freezing point	No data available	
Boiling point / boiling range	100 °C / 212 °F	
Flash point	100 °C / 212 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability or explosive	No information available	
limits		
Lower flammability or explosive	No information available	
limits		
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility in Other Solvents		
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
9.2. Other information		
Softening Point	No information available	
Molecular weight	No information available	
Solvent content (%)	No information available	
Solid content (%)	No information available	
Density	1.125 g/cm ³	
VOC Content (%)	<u>2</u> 0 g/off	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Extremes of temperature and direct sunlight. Keep from freezing.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information	No data available
Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin 1332-58-7	LD50 (Rattus) > 2000 mg/kg	> 5000 mg/kg (Rattus)	1.5 mg/l 4hr
Quartz 14808-60-7	>2000 mg/kg (Rattus)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Symptoms Skin corrosion/irritation Serious eye damage/eye irritation Irritation Corrosivity Sensitization Germ cell mutagenicity Reproductive toxicity Developmental toxicity Teratogenicity STOT - single exposure STOT - repeated exposure	No information available. No information available.
Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
Developmental toxicity	No information available.
Teratogenicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	No information available.
Target organ effects	No information available.
Aspiration hazard	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen. As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

Chemical name	ACGIH	IARC	NTP	OSHA
		Page 6/9		

TSC-300 Outdoor-Indoor Carpet Adhesive

Revision Number 2

Revision date 02-Jan-2020 Supersedes Date: 02-Jan-2020

Quartz 14808-60-7	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Kaolin 1332-58-7	IC 50 (72h) > 1000 mg/l	LC 50 (96h) > 1000 mg/l		EC 50 (48h) > 1000 mg/l (Daphnia magna)

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

Other adverse effects

No information available

IATA

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal of Wastes	It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations	
Contaminated packaging	Dispose of in accordance with federal, state and local regulations	
Section 14: TRANSPORT INFORMATION		
DOT	Not regulated	

Not regulated

IMDG Not regulated

TSC-300 Outdoor-Indoor Carpet Adhesive

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.
Feldspar	68476-25-5

SARA 311/312 Hazard Categories

Classification is shown in section 2 of this SDS

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Revision date	02-Jan-2020
Revision note	SDS sections updated, 2, 3, 11.
Training Advice	No information available
Further information	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation,

TSC-300 Outdoor-Indoor Carpet Adhesive Revision Number 2

Revision date 02-Jan-2020 Supersedes Date: 02-Jan-2020

disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet